



Artificial Lift Production International Corporation

Providing best in class Artificial Lift Systems and Technologies to our customers.

Progressing Cavity Pump Line-Up

		PUMP SERIES																									
		"B" 3"	"C" 3 1/2" Barrel			"D" 3 3/4" Barrel								"E" 4 1/4"		"RJ" RotaJet			"SP" Spira			"F" 5" Barrel			"G" 5.5"	"H" 6.5" Barrel	
Pump Model Metric	m3/day/100rpm	6*	10*	15*	8*	12*	18*	27*	35*	45	48	60	64	80	100	22	35	51	50*	105	140	120	160	200	98	165	200
	Lift Meters*	650	650	650	650	650	650	650	650	650	1200	900	650	900	900	1200	1200	1200	1250	750	600	800	650	500	1200	1200	1200
		1200	1200	1200	1200	1200	1200	1200	1200	1200	1600	1200	1200	1200	1200	1500	1500	1500	1500	900	900	1000	900	700	1600	1600	1600
		1500	1500	1400	1500	1500	1500	1500	1500	1500	1500	1600	1500	1600	1600				1750	1200	1200	1200	1200	900	1800	1800	1800
Pump Model Imperial	bbls/day/100rpm	38*	65*	95*	50*	80*	110*	170*	220*	285	300	380	400	500	630	140	220	320	315*	660	880	755	1000	1250	615	1050	1250
	Lift Feet*	2100	2100	2100	2100	2100	2100	2100	2100	2100	4000	3000	2100	3000	3000	4000	4000	4000	4100	2500	2100	2600	2100	1650	4000	4000	4000
		4000	4000	4000	4000	4000	4000	4000	4000	4000	5300	4000	4000	4000	4000	5000	5000	5000	5000	3000	3000	3300	3000	2500	5250	5300	5300
		5000	5000	4600	5000	5000	5000	5000	5000	5000	5000	5300	5000	5300	5300				5750	4000	4000	4000	4000	3000	6000	6000	6000
Stator	Standard Stator Connection EUE	2 7/8" 73mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	2 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	4 1/2" 114mm	4 1/2" 114mm	4 1/2" 114mm	5.5" LTC 139.7mm	7" LTC 178mm	7" LTC 178mm	
	Optional Stator Connection EUE	3 1/2" 88.9mm	2 7/8" 73mm	2 7/8" 73mm	2 7/8" 73mm	2 7/8" 73mm	2 7/8" 73mm	2 7/8" 73mm	2 7/8" 73mm	2 7/8" 73mm	2 7/8" 73mm	1 7/8" 73mm	2 7/8" 73mm	4 1/2" 114mm	4 1/2" 114mm	4 1/2" 114mm	4 1/2" 114mm	4 1/2" 114mm	4 1/2" 114mm	4 1/2" 114mm	4 1/2" 114mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	4 1/2" 114mm	5.5" LTC 139.7mm	5.5" LTC 139.7mm
Rotor	API Pin	7/8" 22mm	7/8" 22mm	7/8" 22mm	7/8" 22mm	1" 25mm	1" 25mm	1" 25mm	1" 25mm	1" 25mm	1" 25mm	1" 25mm	1" 25mm	1" 25mm	1" 25mm	1" Box 25mm	1-1/8" 28mm	1-1/8" 28mm	1" 25mm	1" 25mm	1" 25mm	1 1/8" 28mm	1 1/8" 28mm	1 1/8" 28mm	1 1/8" 28mm	1 1/8" 28mm	1 1/8" 28mm
	Minimum Tubing to Surface EUE	2 3/8" 84mm	2 3/8" 84mm	2 3/8" 84mm	2 3/8" 84mm	2 7/8" 73mm	2 7/8" 73mm	2 7/8" 73mm	2 7/8" 73mm	2 7/8" 73mm	2 7/8" 73mm	1 7/8" 73mm	2 7/8" 73mm	3 1/2" 88.9mm	3 1/2" 88.9mm	2 7/8" 73mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	2 7/8" 73mm	2 7/8" 73mm	2 7/8" 73mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	5 1/2" 139.7mm Casing
Tubing	Minimum Tubing Above Stator EUE	2 7/8" 73mm	2 7/8" 73mm	2 7/8" 73mm	2 7/8" 73mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	2 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	4 1/2" 114mm	4 1/2" 114mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	4 1/2" 114mm	4 1/2" 114mm	4 1/2" 114mm	4 1/2" 114.3mm	7" 178mm Casing	7" 178mm Casing
	Rotor Orbit Diameter	1.9" 48mm	2.3" 59mm	2.4" 61mm	2.3" 59mm	2.5" 64mm	2.6" 66mm	2.6" 66mm	2.6" 66mm	2.8" 71mm	2.8" 71mm	2.8" 71mm	2.8" 71mm	3.3" 71mm	3.3" 74mm	2.8" 71mm	3.1" 79mm	3.1" 79mm	2.7" 69mm	2.9" 74mm	2.9" 74mm	3.8" 97mm	3.8" 97mm	3.8" 97mm	3.8" 97mm	5.0" 127mm	5.25" 134mm

* Pump Series are coailable

Pump Series in Red can be installed into 3 1/2" lined tubing

SP- Spira Pumps are Uniform Wall

RJ - Patented RotaJet PCP Hollow Rotor System



Exclusive Partnership